

PFI-T435 LRF Thermal Monocular Camera



Key Features

- Vanadium oxide uncooled focal plane detector.
- Compatible with 10x daylight scope.
- 0.9 cm@100 m high accuracy click value.
- Robust Mg alloy housing.
- Bluetooth remote controller included.
- Ergonomic buttons layout.
- Crystal breathing power button.
- Carbon fiber decorative texture design.
- FHD OLED display.
- Replaceable 18650 battery.
- IP67 rated.

Technical Specification

Thermal	
Detector Type	Vanadium oxide uncooled focal plane detector
Effective Pixels	384 (H) × 288 (V)
Pixel Pitch	12 μm
Spectral Range	8 μm–14 μm
Sensitivity (NETD)	≤18 mK@f/1.0, 25°C
Focal Length	35 mm
Aperture	F1.0
Field of View	H: 7.8°; V: 5.9° / H: 13.7 m; V: 10.3 m (@100 m)
Focus Control	Manual
Close Focus Distance	3.0 m (9.84 ft)
Detection Distance	1,800 m (5,905.51 ft)
Magnification	1.0 ×
Frame Rate	50 Hz
Display	
Screen	1920 × 1080, 0.49 inch, OLED
Color Palettes	6 (white hot/black hot/iron red/alarm/emerald/amber)
Video Compression	H.264
Eye Relief	30 mm (1.18")
Exit Pupil	25 mm (0.98")
Function	
Video Recorder	Yes
Snapshot	Yes
Wi-Fi Hotspot	Yes
Hot Spot Track	Yes
Video Distance Measurement	Yes
FFC Calibration	Auto; manual; external correction
Blue Tooth Remote Controller	Yes
Standby Mode	Yes
DPC (Defective Pixel Correction)	Yes
Storage	Built-in 32 GB
Click Value	X: 0.9 cm@100 m; Y: 1.8 cm@100 m
Laser Range Finder	
Distance	1,000 m (3,280.84 ft)

Accuracy	±1 m (3.28 ft)
Power	
Battery Type	Rechargeable 18650 battery
Battery Life	7 h@25 °C
Power Supply	5 VDC/2 A
Port	USB Type-C
Overvoltage Protection	Yes
General	
Operating Temperature	-30 °C to +55 °C (-22 °F to +131 °F)
Operating Humidity	≤95%
Protection Grade	IP67
Max. Recoil	6,000 J
Packaging Dimensions	293.0 mm × 180.0 mm × 138.0 mm (11.54" × 7.09" × 5.43") (L × W × H)
Product Dimensions	126.0 mm × 95.5 mm × 71.7 mm (4.96" × 3.76" × 2.82") (L × W × H)
Gross Weight	<2.3 kg (5.07 lb)
Net Weight	545 g (1.20 lb)

Dimensions (mm[inch])

