

PFI-SA50 Thermal Monocular Camera



Key Features

- Vanadium oxide uncooled focal plane detector.
- Ergonomic buttons layout.
- Crystal breathing power button.
- Carbon fiber decorative texture design.
- FHD OLED display.
- Replaceable 18650 battery.
- High optical magnification.
- Connects to the mobile app through Wi-Fi.
- Six color palettes.
- Built-in EMMC (64 GB).
- IP67 rated.

Technical Specification

Thermal	
Detector Type	Vanadium oxide uncooled focal plane detector
Effective Pixels	1280 (H) × 1024 (V)
Pixel Pitch	12 μm
Spectral Range	8 μm–14 μm
Sensitivity (NETD)	≤15 mK@f/1.0, 25 °C
Focal Length	50 mm
Aperture	F1.0
Field of View	H: 17.2°; V: 13.8°/H: 30.7 m; V: 24.6 m (@100 m)
Focus Control	Manual
Close Focus Distance	3 m (9.84 ft)
Detection Distance	2,600 m (8,530.18 ft)
Recognition Distance	662 m (2,171.92 ft)
Identification Distance	331 m (1,085.96 ft)
Magnification	1.72×
Frame Rate	50 Hz
Display	
Screen	1920 × 1080, 0.49 inch, OLED
Color Palettes	6 (white hot/black hot/iron red/alarm/emerald/amber)
Video Compression	H.264
Diopter	–5D to +3D
Eye Relief	15 mm (0.59 inch)
Exit Pupil	8 mm (0.31 inch)
Function	
Digital Zoom	1x, 2x, 4x, 8x
Video Recorder	Yes
Snapshot	Yes
Wi-Fi Hotspot	Yes
Hot Spot Track	Yes
FFC Calibration	Auto, Manual, External Correction
Standby Mode	Yes
DPC (Defective Pixel Correction)	Yes
MIC	Yes
Compass	Yes

Storage	Built-in 64 GB
Power	
Battery Type	Replaceable 18650 battery
Battery Life	4.5 h@25 °C (Wi-Fi off)
Power Supply	5 VDC/2 A
Port	USB Type-C
Overvoltage Protection	Yes
General	
Operating Temperature	-30 °C to +55 °C (-22 °F to +131 °F)
Operating Humidity	≤95%
Protection Grade	IP67
Packaging Dimensions	291 mm × 140 mm × 127 mm (11.46" × 5.51" × 5") (L × W × H)
Product Dimensions	208.4 mm × 70 mm × 80.9 mm (8.2" × 2.76" × 3.19") (L × W × H)
Gross Weight	1.28 kg (2.82 lb)
Net Weight	544 g (1.20 lb)

Dimensions (mm[inch])

